BGM400 Barrier Gate

Speed Adjustable, High Stability

BGM400 series barrier gate is driven by high-performance brushless DC motor, stable running, low noise, stable and reliable performance. The gate control system is rich in intefaces, widely used in all kinds of parking lot entrance and exit channel management.

Features

- Highly energy-efficient because of the DC brushless motor
- Digital control mainboard with diverse configuration possibilities
- The barrier arm will rebound when an obstacle detected
- Reversible boom direction
- Delay automatic close
- Manual rise and fall in case of absence of power
- Traffic light signal output
- Failure warning

Specifications

Model	BGM400L/R
Operating Speed	1.5s to 6s
Boom Length	3m to 6m
Boom Type	Telescopic straight boom
Motor Type	DC 24V brushless motor
Output Power	160W
Output Current	10A
Operating Voltages	DC 24V
Power Supply	AC 220V/110V, 50Hz to 60Hz
MCBF	2 million times
Remote Control Distance	≤30m
Operating Temperature	-30℃ to 75℃
Protection Level	IP54
Chassis Dimensions (mm)	330*265*980mm
Net Weight (excluding the barrier arm)	40kg

Dimensions (mm)



Directions





L：The chassis on the left, the boom on the right

R：The chassis on the right, the boom on the left

Related Products

1	2	3	4	5	6	7	8
LPRS1000	Parking Warning Light	VR10 Pro	PSA02 Vehicle detector	PSA26 Photocell	UHF 5/10 Pro	PSA03 Loop coil	Manual Button
For the management of entrance and exit channels	For the traffic indication	For safety detection and automatic closing trigger	For safety detection and automatic closing trigger	For anti-smash detection	For the management of entrance and exit channels	For vehicle detection(Use with PSA02)	For emergency switch control

ZKTECO CO.,LTD. www.zkteco.com E-mail: sales@zkteco.com

Copyright©2023 ZKTECO CO., LTD. All rights reserved.